

LIXUS®-d Systemreihe

Digitale Zeilenkameras

Kamera	Option	Pixel- anzahl	Pixel- maße [$\mu\text{m} \times \mu\text{m}$]	aktive Länge [mm]	Transfer- kanäle je 8 Bit RS422/ RS644	Pixel- takt [MHz]	maximale Scanrate [Scans/s]	Anti- Bloom.	Shutter	Min. Belicht.zeit [μs]	Objektiv- anschluß					Abmessungen [mm ³]
											C- Mount	F- Mount	Nikon	M72 x 1	Mamiya	
LIXUS-d 256	-S -D	256	14 x 14	3,6	1 2	20 2 x 15	65.000 111.000	x	x	4,0 3,0	x	o	o	o	o	86 x 86 x 170
LIXUS-d 512	-S -D	512	10 x 10	5,1	1 2	20 2 x 20	32.360 64.700	x	x	4,0 2,0	x	o	o	o	o	86 x 86 x 170
LIXUS-d 1024	-S -D	1024	10 x 10	10,2	1 2	20 2 x 20	17.700 35.400	x	x	4,0 2,0	x	o	o	o	o	86 x 86 x 170
LIXUS-d 2048	-S -D	2048	10 x 10	20,5	1 2	20 2 x 20	9.280 18.570	x	x	4,0 2,0		x	o	o	o	86 x 86 x 184
LIXUS-d 2048C		2048	14 x 14	28,7	1	5	2.380		x	5,0		x	o	o	o	86 x 86 x 184
LIXUS-d 4096	-S -D	4096	10 x 10	40,96	1 2	20 2 x 20	4.757 9.514	x	x	4,0 2,0		x	o	o	o	86 x 86 x 184
LIXUS-d 5000		5000	7 x 7	35,0	1	8	1.580			630		x	o	o	o	86 x 86 x 184
LIXUS-d 5150	-S -D	5150	7 x 7	36,1	1 2	20 2 x 15	3.750 5.630			270 180		x	o	o	o	86 x 86 x 184
LIXUS-d 6144	-S -D	6144	7 x 7	43,0	1 2	20 2 x 15	3.210 4.810	x	x	4,0 3,0		x	o	o	o	86 x 86 x 184
LIXUS-d 7500	-S -D	7500	7 x 7	52,5	1 2	20 2 x 15	2.600 3.900			380 260		o		x	o	86 x 86 x 197
LIXUS-d 7926		7926	7 x 7	55,5	1	8	990			1000		o		x	o	86 x 86 x 197
LIXUS-d 8192	-S -D	8192	7 x 7	57,3	1 2	20 2 x 15	2.410 3.620	x	x	4,0 3,0		o		x	o	86 x 86 x 197

x – Standard o – Option

Technische Änderungen und Irrtum vorbehalten.